

Mechanical

Dimensions 117.1 x 90 x 21.2 mm (4.6 x 3.5 x 0.8")

Weight 206 g (7.3 oz)

Enclosure material Polycarbonate

Hardware

Management interface Ethernet In-Band

Networking interface (5) 1/2.5 GbE RJ45 ports

Total non-blocking throughput 12.5 Gbps

Switching capacity 25 Gbps

Forwarding rate 18.6 Mpps

Power method (1) AC power adapter, 5V DC, 1A
(1) PoE (PairA 1, 2+; 3, 6-)(PairB 4, 5+; 7, 8-)

Power supply External AC/DC adapter
UniFi PoE switch

Supported voltage range AC/DC input: 5V DC
PoE input: 44—57V DC

Max. power consumption AC/DC input: 5W
PoE input: 6.4W

Button Factory reset

Ambient operating temperature -20 to 45° C (-4 to 113° F)

Ambient operating humidity 10 to 90% noncondensing

Certifications CE, FCC, IC

Switching Features

Layer 2 features STP / RSTP with priorities and port-level disable
Port isolation
Storm control
Port mirroring
Multicast / broadcast rate limiting
Flow control
Jumbo frames
Egress rate limit

Layer 3 features —

LEDs

System

(1) Blue/white: power
Blinking white: bootup in progress
Blinking blue: firmware upgrading
Steady white: factory defaults; unit is awaiting adoption
Steady blue: unit is adopted

Ethernet

(5) Green: link/activity

Application Requirements

UniFi Network

Version 8.4.62 and later